



Form Attachment 01;VA027	DECLARATION OF PERFORMANCE According to Annex III of Regulation (EU) No. 305/2011 (Construction Products Regulation)	 KLEIBERIT® <small>KLEBSTOFFE • ADHESIVES</small>
Page:1/2		

Declaration of Performance No.: 5665-01-1-2014	
1.	Unique identification code of the product type: KLEIBERIT Supracraft PUR 566 (white)
2.	Type, batch or serial number of any other element allowing identification of the construction product as required pursuant to Article 11 (4): Batch description see label on packaging
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: 1 component adhesive and sealant compound based on polyurethane; non-load bearing sealant for indoor and outdoor application: Facade: Type F – ext-int CC, Pedestrian Paths Type PW ext-int CC
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): Klebchemie M. G. Becker GmbH & Co. KG Max-Becker-Straße 4 76356 Weingarten / Baden
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): not applicable / not relevant
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
7.	In case of the declaration of performance concerning a construction product covered by a harmonized standard: Ginger CEBTP NB-No. 0074 performed the initial tests under System 3 and issued the test report.
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not applicable / not relevant

Form Attachment 01;VA027	DECLARATION OF PERFORMANCE According to Annex III of Regulation (EU) No. 305/2011 (Construction Products Regulation)	
Page:2/2		

9.	Declared performance: Conditioning: Procedure B; substrate: glass, aluminum without primer	
	essential characteristics	Performance
	Fire classification (EN 13501)	Class E
	Stability (EN ISO 7390)	≤ 3 mm
	Volume loss (EN ISO 10563)	≤ 10 %
	Tensile stress after immersion in water (23°C) (EN ISO 10590)	NF
	Tensile stress after immersion in water (after 28 days) (EN ISO 10590)	NF
	Tensile stress after immersion in saltwater (after 28 days) (EN ISO 10590)	NF
	Tensile stress at – 30°C (EN ISO 8340)	NF
	Tensile strength, (EN ISO 8340)	Pass
	Durability (ISO 8339, ISO 9047 ISO 10590)	Pass
Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: Not applicable		
10.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.	
Signed for and on behalf of the manufacturer by: Dr. Achim Hübener, Managing Director <hr/> (name and function) Weingarten, 04.06.2014 <hr/> (place and date of issue)		
<div style="text-align: right;"> <hr/> (signature) </div>		