

KLEIBERIT 657.0.10

UV curing top coat for roller application, super matt

Fields of Use

- Photosensitive UV top coat for the KLEIBERIT HotCoating® technology for high scratch resistance and gloss levels of < 5 units.

Characteristics of 657.0.10

Base:	UV curing acrylates
Specific weight (at 20 °C):	approx. 1.11 g/cm ³
Solids:	>99 % (theoretical value)
Colour:	uncolored, typical
Gloss level < 60°:	< 5 units The gloss level depends on the processing parameters.
Viscosity at delivery (at 20 °C)	
6mm DIN cup:	25 - 35 seconds
Identification:	Identification is required according to EU regulations (See our safety data sheet)

Processing

Ambient and substrate processing temperature: 22 - 28 °C
 Application with roller applicator: 25 - 30 g/m²
 Application viscosity: viscosity at delivery

Stir well before use.

All process relevant properties must be checked before processing.

Drying / UV-Curing

Pre-curing: excimer
 Curing: 10 m/min
 UV-Dosage*: 800 - 1200 mJ/cm² (Hg)

* The stated UV dosages are empirical values based on measurements with „UV-Disc A002400 (Full-UV: 250 – 410 nm)“ by UV-Technique

It is absolutely necessary to determine the processing conditions for optimal result before starting production.

These depend on the equipment technology as well as on the substrate to be coated. The final characteristics like adhesion, scratch resistance and sandability have to be monitored continuously.

Cleaning

Soiled application tools and machinery parts to be cleaned immediately with KLEIBERIT 820.0.

Packaging

KLEIBERIT 657.0.10
 metal pail, 25 kg net
 IBC container, 1,000 kg net

Cleaner

KLEIBERIT 820.0
 metal can, 22 kg net

Additional packaging sizes available upon request.

Storage

Shelf life in factory sealed containers (at 5 - 25°C) is at least 9 months.
 Storage at high temperatures can shorten the shelf life.

Recommended transport temperature -10 - 35 °C.

Protect from light, heat and frost.

Version 07/08/2019 al; replaces previous versions

KLEIBERIT 657.0.10

Adhesive and Waste Disposal

Waste Code 080111

Our containers are made of recyclable material. Well drained containers can be recycled.

Service

Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation.